



East Asia Enviro SDN BHD (909959-K)
PMT 1159, LORONG PERUSAHAAN BUKIT MINYAK 22
PENANG SCIENCE PARK, 14100 SIMPANG AMPAT, PENANG
MALAYSIA
Tel: (604) 5057883 Fax: (604)-5059883

SAFETY DATA SHEET

Page : 1 of 6
Revised Date : Feb 11, 2022
Prepared Date : July 31, 2017

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: Refrigerant Gas (R410A)
Synonyms: HFC-410A, Akashifron R410A
Manufacturer: East Asia Enviro Sdn. Bhd.
Address: PMT 1159, Lorong Perusahaan Bukit Minyak 22
Penang Science Park, 14100 Simpang Ampat,
Penang Malaysia
Emergency Phone: 60-4-5057883 (Office Hour)

2. HAZARDS IDENTIFICATION

Classification of the substance / mixture Gases under pressure, liquefied gas



Label Elements:

Hazard statements:	H280: Contains gas under pressure; may explode if heated.
Storage Precautionary: statements	P410 + P403 Protect from direct sunlight. Store in a well-ventilated location.
Other hazards:	Vapors are heavier than air and may cause suffocation due to depletion of oxygen necessary for breathing. Cylinders may rupture under fire conditions. Decomposition may occur.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name:	Pentafluoroethane	Difluoromethane		
Chemical Formula:	CHF_2CF_3	CH_2F_2		
<u>Chemical Name</u>	<u>Chemical Formula</u>	<u>CAS No.</u>	<u>EC No.</u>	<u>Typical Wt %</u>
Pentafluoroethane	CHF_2CF_3	354-33-6	206-557-8	50
Difluoromethane	CH_2F_2	75-10-5	200-839-4	50

4. FIRST AID MEASURES

4.1 Eyes:

In the event of contact with eye/eyes, eye irritation or blurring of vision may occur.

SAFETY DATA SHEET

Page : 2 of 6
Revised Date : Feb 11, 2022
Prepared Date : July 31, 2017

Measures: Flush affected eye/eyes with running water for at least 15 minutes. If a contact lens is in place, remove it immediately or whenever able to. Use physiological saline if readily available. Keep affected eyelid/s open to allow evaporation of product. Consult an ophthalmologist in case of persistent ailment, seek medical attention if necessary.

4.2 Skin:

In the event of contact with skin, liquid may cause frostbite. Prolonged overexposure may cause de- fatting or dryness to affected skin area.

Measures: If in case of contact, allow evaporation of product before flushing affected area with lukewarm water. Do not use hot water. Contact a physician in case of persistent ailment, seek medical attention if necessary.

4.3 Inhalation:

Inhalation of high concentration of vapor is harmful and may cause heart irregularities, unconsciousness or death. Intentional misuse or deliberate inhalation may cause death without warning. Prolonged direct exposures may lead to temporary alteration of the heart's electrical activity with irregular pulse, palpitations, or inadequate circulation. Gross exposure may be fatal.

Individuals with pre-existing diseases of the central nervous or cardiovascular system may have increased susceptibility to the toxicity of excessive exposures.

Inhalation may include temporary nervous systems disorders such as depression. Other anesthetic effects such as dizziness, headache, confusion, in-coordination and loss of consciousness may also occur.

Measures: If in the event of inhalation, immediately evacuate affected personnel to open air area with sufficient fresh air. If not possible to access personnel, do not attempt aid unless personal breathing apparatus is available. Artificial ventilation by blowers or fans may be required. If affected personnel is conscious, try to keep personnel clam. If not breathing, give artificial respiration. If difficulty in breathing is observed, give oxygen if available. Seek medical attention if necessary.

4.4 Ingestion: If in the remote event of accidental ingestion, seek immediate medical attention.

4.5 Notes to Physicians: This material may cause heart to be more susceptible to conditions such as Arrhythmias. Catecholamine such as adrenaline and other compounds having similar effects are advised to be reserved for emergencies and only to be used with exceptional caution.

5. FIRE-FIGHTING MEASURES

Upper, Flammable Limits in Air (% by volume): Not applicable

Lower, Flammable Limits in Air (% by volume): Not applicable

Flash point: Will not burn

Auto-ignition Temperature: Not determined

Extinguishing Media:

Use extinguishing media appropriate to extinguish or contain fire conditions.

SAFETY DATA SHEET

Page : 3 of 6
Revised Date : Feb 11, 2022
Prepared Date : July 31, 2017

Specific Hazards:

Contact of welding or soldering torch flame with high concentrations of refrigerant can result in visible changes in the size and color of torch flames. This flame effect will only occur in concentrations of product well above the recommended exposure limit, therefore stop all work and ventilate to disperse refrigerant vapor from work area before using any open flame.

Mixtures of R410A with high concentrations of air at elevated pressure can become combustible at ambient temperature. As the temperature of the mixture is increased, lower pressure (but still greater than atmospheric pressure) can create the same effect. Therefore, R410A should not be mixed with air under pressure for leak testing or other purposes. In general, R410A should not be used or allowed to exist with high concentrations of air above atmospheric pressure.

Protection Actions For Fire Fighting Instructions:

Use water spray or fog to cool containers. Self –contained breathing apparatus (SCBA) is required if cylinders rupture or contents are released under fire conditions. Water runoff should be contained and neutralized prior to release.

Other Precautions

If safe to do so, remove the exposed containers, or cool with water.
If under fire conditions, avoid unnecessary proximity, maintain safe evacuation distance. Only attempt to ventilate and clean the rooms if there is no imminent danger present.

6. ACCIDENTAL RELEASE

MEASURES Personal Precautions:

Avoid contact with skin and eyes.
Do not smoke or light any open flames.
Do not breathe in the vapors.
Review firefighting measures given in section 5 before proceeding with clean up.
Use appropriate personal protective equipment.
Work from upwind, if possible.

Methods and materials for containment and cleaning up:

Prevent the product from spreading into the environment. Shut off the source of R410A. Ventilate spillage area, especially low or enclosed places where heavy vapors may collect and concentrate. Restrict access to the area until completion of the clean-up procedure.
Let the product evaporate.
Remove open flames.
Use self-contained breathing apparatus (SCBA) for large spills or releases.

7. HANDLING AND STORAGE

Precaution for Safe Handling:

Avoid inhalation of vapors. Avoid liquid contact with eyes and skin. Use with sufficient ventilation to keep employee exposure below recommended limits. R410A should not be mixed with air for leak testing. In general, product should not be in area whereby high concentrations of air above atmospheric pressure is present. Contact with chlorine or other strong oxidizing agents should also be avoided.

Conditions for Storage: Keep in a clean, dry area. Do not heat above 52°C (125°F).

SAFETY DATA SHEET

Page : 4 of 6
Revised Date : Feb 11, 2022
Prepared Date : July 31, 2017

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls:

Avoid inhalation of vapors. Avoid contact with skin or eyes. Use with sufficient ventilation to keep employee exposure below recommended exposure limit. Local exhaust should be used if large amounts are released. Mechanical ventilation should be used in low or enclosed places.

Personal Protective Equipment:

Impervious gloves should be used to avoid prolonged or repeated exposure. Chemical splash goggles should be available for use as needed to prevent eye contact. Under normal manufacturing conditions, no respiratory protection is required when handling this product, unless ventilation is inadequate. Self-contained breathing apparatus (SCBA) is required if large release occurs.

Exposures Guidelines:

Pentafluoroethane	ACGIH (TLV)	None Established
	OSHA (PEL)	None Established
	AIHA (WEEL)	1000 ppm, 4900mg/m ³ , 8 hr TWA
Difluoromethane	AIHA (WEEL)	1000 ppm 8 hr TWA

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical Data

Appearance	Clear, Colorless liquid and vapor
Odor	Slightly ethereal
pH	Neutral
Boiling Point	-48.5°C (-51.54°F) @ 760 mmHg
Freezing Point	Not determined
Vapor Pressure	215.3 psia @ 25°C (77°F) Saturated
Vapor Density	3.0 @ 25°C (77°F) (Air=1)
Specific Gravity	1.08 @ 25°C (77°F) (H ₂ O=1)
Solubility in Water	Unknown
Molecular Weight	72.6

10. STABILITY AND REACTIVITY

Chemical Stability: This material is chemically stable under specific conditions, storage shipment and/or use.

Conditions to avoid: Open flames and high temperatures.

Incompatibility with other materials: Incompatible with alkali or alkaline earth metals – powdered Al, Zn, Be, etc

SAFETY DATA SHEET

Page : 5 of 6
Revised Date : Feb 11, 2022
Prepared Date : July 31, 2017

Possibility of hazardous reaction & products: This material can be decomposed in high temperatures (open flames, glowing metal surfaces, etc) thus, forming hydrochloric and hydrofluoric acids, and possibly carbonyl halides. These materials are toxic and irritating. Contact should be avoided.

Polymerization: Will not occur

11. TOXICOLOGICAL INFORMATION

Pentafluoroethane:

Inhalation, follow by intravenous injection of epinephrine to simulate stress reactions, resulted in cardiac sensitization in dogs. Following repeated inhalation exposure, no adverse effects were observed in rats. No birth defects were noted in the offspring of rats or rabbits exposed by inhalation during pregnancy. No genetic changes were observed in standard tests using animal cells, whole animals or bacteria. Single exposure (acute) studies indicate:

Inhalation – Practically non-toxic to rats (4-hr LC50 > 800,000ppm)

Difluoromethane:

Inhalation, follow by intravenous injection of epinephrine to simulate stress reactions, resulted in cardiac sensitization in dogs. Acute inhalation of high concentrations has produced an anesthetic effect in rats. Following repeated inhalation exposure adverse effects were observed in rats. No birth defects were noted in the offspring of rats or rabbits exposed by inhalation during pregnancy, no birth defects were noted in the offspring of rats or rabbits exposed by inhalation during pregnancy, even at dosages which produced significant adverse effects in the mother. No genetic changes were observed in standard tests using bacteria, animal cells or whole animals. Single exposure (acute) studies indicate:

Inhalation – Practically non-toxic to rats (4-hr LC50 > 520,000ppm)

12. ECOLOGICAL INFORMATION

Aquatic Toxicity:

48 hour EC50 – Not determined

96 hour LC50 – Not determined

ODP: 0

GWP: 2000 (relative to carbon dioxide for integration of 100years)

13. DISPOSABLE CONSIDERATIONS

Prohibition

Do not allow the product to be released to the environment.

Waste Disposal

Comply with local regulations. Reclaim by distillation or remove to a permitted waste facility.

SAFETY DATA SHEET

Page : 6 of 6
Revised Date : Feb 11, 2022
Prepared Date : July 31, 2017

14. TRANSPORTATION INFORMATION

Shipping Information

DOT/IMO
Hazard Label



Proper Shipping Name : Liquefied gas, N.O.S. (Pentafluoroethane, Difluoromethane)
DOT Name : Refrigerant Gas R-410A
IMO Class (Hazard Class) : 2.2
UN no. : 3163
DOT/IMO Label : Non-Flammable Gas

15. REGULATORY INFORMATION

Hazard Categories under SARA Title III Rules (40CFR Part 370)

Acute : Yes
Chronic : Yes
Fire : No
Reactivity : No
Pressure : Yes

EC Labeling/Classification

Hazard Symbol: N

Safety (S) Phrases:

S47: Keep at temperature not exceeding 52°C.
S41: In case of fire and/or explosion do not breathe fumes.
S57: Use appropriate containment to avoid environmental contamination
S59: Refer to manufacturer/supplier for information on recovery/recycling
S61: Avoid release to the environment. Refer to special instructions/safety data sheet.

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the Safety Data Sheet. The user's attention is drawn to the possible existence of additional provisions, which complete these regulations. Refer to all applicable National, International and Local regulations or provisions.

16. OTHER INFORMATION

The information in this Safety Data Sheet only concerns the above-mentioned product and does not relate to use with other product(s) or in any process. This information is to our best present knowledge correct and complete and is given in good faith but without warranty. It remains the user's own responsibility to ensure that the information is appropriate and correct for his special use of this product.

“Akashifron” is a registered trademark.

This copy of SDS supersedes previous copies.